

SOLA



SOLA series luminaires are the ideal solution for fulfilling requirements of functional street lighting and residential areas. Equipped with high-quality electrical components, long lifetime is assured. Tool-free design enables easy, safe and minimal cost for maintenance and installation.

SOLA series offers a reliable way to reduce energy consumption and create a more attractive urban living environment with visual comfort for public and residential areas.



SOLA



Luminous flux	9000lm - 25000lm
Correlated color temperature	3000K, 4000K, 5000K, 6000K
Light source	Integral LED module
Housing	ADC12 die-cast aluminium
Cover	Toughened 6mm glass (IK09)
Screws	304 stainless screws
Driver	Tridronics / Meanwell / Signify
Electrical	Class I or Class II
Input voltage	90-305VAC / 50-60Hz ; 170-305VAC / 50-60Hz
Surge protection	6KV, 10KV or 20KV
Dimming	Dali / 1-10V / PWM / AstroDIM / Zhaga/ NEMA/ D4i
External cable	10m, 12m, 15m, 18m
Installation bracket diameter	60mm
Compatibility of pole diameters	48/60mm (76mm with adapter)
Lifetime	100,000 hours (at 25°C).
Operating temperature	-40° to 50°C.
Light fitting protection	IP66;IK09
Dimensions	777mm / 1019mm - 330mm/440mm - 125/145mm
Standards	IEC/EN
Country of origin	Made in EU

OPTIONAL FEATURES

- Photocell
- Motion detection
- Smart control device
- Smart city equipment
- Zhaga socket / Nema socket (with 3, 5 or 7 pins)



SOLA

Name	Luminous flux netto (lm)	Power (W)	Efficacy (lm/W)	Standard CCT (K)
SOLA STREET / AREA 70	9000	70	128	4000
SOLA STREET / AREA 90	12000	90	133	4000
SOLA STREET / AREA 110	14500	110	131	4000
SOLA STREET / AREA 140	18000	140	128	4000
SOLA STREET / AREA 190	25000	190	131	4000

