

# LINA



<b>Luminous flux</b>	4374*-13445lm*
<b>Correlated colour temperature</b>	4000K(3000K, 5000K and 6000K)
<b>Power</b>	20W-120W
<b>Light source</b>	Integrated LED module
<b>Optics</b>	DK-173-160X80-TPII-M-H-12H1-5050-B
<b>Housing</b>	ADC12 aluminium die-cast
<b>CRI</b>	> 70
<b>Insulation safety class</b>	Class I/II
<b>Compatibility of pole diameters</b>	50-60mm and 60-76mm
<b>Input voltage</b>	90-305VAC/50-60Hz, 170-305VAC/50-60Hz
<b>Light fitting protection</b>	IP66; IK10
<b>Dimming</b>	DALI / 1-10V/ AstroDIM
<b>Lifetime</b>	L90B10 for 100 000 hours (Ta 25°C)
<b>Operating temperature</b>	-40°C to 50°C
<b>Dimensions</b>	Size S (380x380x112)* Size L (560x560x288)*
<b>Certificates</b>	CE, LVD, EMC, RoHS, TM-21

## Tolerance +/- 7%

Name	Luminous flux net (lm)	Power (W)	Efficiency (lm/W)	Standard CCT (K)
LINE (SL58) 20W	2935	20.1	145.2	4000
LINE (SL58) 30W	4374	30.1	145.3	4000
LINE (SL58) 35W	5104	35.2	145	4000
LINE (SL58) 40W	5899	40.6	145.3	4000
LINE (SL58) 50W	7396	50.9	145.3	4000
LINE (SL58) 60W	8892	61.2	145.3	4000
LINE (SL58) 90W	13445	92.6	145.2	4000

