

TELOS

- Industrial LED light fitting made of aluminium section with **high chemical resistance** and diffuser made of tempered safety glass.
- Suitable for industrial indoor and outdoor roofed spaces, warehouses, garages, workshops, sports areas, transport terminals, utility structures, agricultural operations and laboratories without a danger of explosion of gases, dust and combustible fumes.
- Resistant to deformation, dust, spouting water and chemically aggressive environment
- Maximum ambient temperature: $t_a = 35\text{ }^{\circ}\text{C}$.
- Lifetime of 50,000 hours (L90B10).
- Light fitting protection: IP66 & IK10.



IP66

230 V
0/50/60
Hz

TECHNICAL INFORMATION

Diffuser: tempered glass

Body: grey aluminium profile, surface treated with powder-coated colour

Reflector: steel sheet, white colour (RAL 9003)

Clips: stainless steel




Sealing: polyurethane sealing (PUR) in body groove

Cable glands: brass M18 x 1,5

Terminal block: screwless, three-pole (basic version)

Side covers: grey aluminium alloy with plastic side plates for fixation and suspension of glass at assembly, surface treated with powder-coated colour

Type	Ta. Max (°C)	Luminous flux light fitting (lm)	Power (W)	Efficacy (lm/W)	Net weight (kg)	Luminaire length (mm)
TELOS 2600	35	1950	18	108	2	624
TELOS 3200	35	2420	22	110	2	624
TELOS 4400	35	3320	30	111	2	624
TELOS 5200	35	3870	35	111	4	1224
TELOS 6400	35	4760	42	113	4	1224
TELOS 8800	35	6660	58	115	4	1224
TELOS 6500	35	4880	44	111	5	1524
TELOS 8000	35	5960	53	112	5	1524
TELOS 11000	35	8150	71	115	5	1524



OPTIONAL FEATURES

- Side hanger for wall mounting and positioning
- DALI adapter: Digital dimmable driver